

RPFL SuperDek® Colorbond® XRW/Ultra 0.42BMT/0.48BMT Roof cladding. Base Materials: Steel Grade G550. BMT 0.42.Mass 4.3kg/m2 or 0.48BMT 4.9kg/m2. AZ 150 coating for XRW & AZ 200 coating for Ultra. Profiles tested for Cyclonic Conditions.


RPFL Non Std Colorbond® XRW/Ultra 0.55 BMT Flashing Base Materials: coating AZ200 Steel Grade G300. fixed to the roof cladding with SDM Screw.

RPFL SuperDek® Colorbond® XRW/Ultra 0.42BMT/0.48BMT Wall cladding. Base Materials: Steel Grade G550. BMT 0.42.Mass 4.3kg/m2 or 0.48BMT 4.9kg/m2. AZ 150 coating for XRW & AZ 200 coating for Ultra. Profiles tested for Cyclonic Conditions.

Notes:

All installation to be as per New Zealand steel specification and installation guide. (March 2011) & New Zealand roof and cladding CODE OF PRACTICE (Version 2.2/2012)

R P F L	Profiles (Fiji) Pte Ltd and must not be copied or disclosed to any third party without the written consent of the company. ALL DIMENSIONS ARE IN mm UNLESS	PROJECT TITLE: ROOF DETAILS	DRAWN:	C.V.B	SCAL
Roofing & Profiles (Fiji) Pte Ltd		DRAWING TITLE:	DATE :	09/12/2020	REVIS
Ph: (679) 6673764 M: 999 9309 Email:info@roofingandprofiles.com.fj		SHOP DRAWINGS	CHECKED BY:		APPR



LE: 1:5 @ A4	SHEET No: SD 1150	
ISION No: F	REVISION TITLE:	
ROVED BY:	JOB NUMBER: 13 - RAIN	